



# ABLE DOOR SERVICES (NSW) PTY LTD

## PRODUCT SPECIFICATIONS

### Slats:

50, 75 or 100mm high and are available in three different gauges 0.6mm, 0.8mm and 1.0mm galvanised steel.

100mm Slat MATERIAL THICKNESS mm	RECOMMENDED MAXIMUM OPENINGS	
	Height MM	Width MM
0.6	5000	5000
0.8	6000	6000
1.0	10000	10000

### Drum:

The drum shall be manufactured from 150nb or 200nb ERW pipe with a 35mm or 38mm CS1020 bright bar axle with hexical oil tempered springs to balance the door.

We also produce spring-less drums for dead lift applications.

### Guides:

- Standard sizes 50mm x 1.9mm galvanised
- 75mm x 1.9mm galvanised
- 100mm x 1.9mm galvanised
- 100mm x3mm wind lock guide galvanised
- 100mm heavy duty wind lock guide fabricated to suit application

### Bottom Rail:

- Standard is extruded aluminium T section with weather seal
- Optional Bottom Rails – Galvanised steel angle or box section bottom rails (weather seal optional)

### Locking:

- Motorised doors are not recommended to have locks
- Sliding pad bolts (inside or outside)

### Operation:

- Hand operated up to 5 square meters
- Manual chain operated up to 36 square meters
- Electric Operation on all doors using 1hp, 1.5hp or 2hp motors in 240v or 3 phase power supply with manual emergency chain override
- Remote control option also available

### Finish Options:

- Galvanised standard finish
- Polyurethane Paint on site
- Powder coat prior to installation

Full range of available colours viewable on our website [www.abledoors.com.au/finishes.html](http://www.abledoors.com.au/finishes.html)